

Baferi za toplotne pumpe (TP) od čeličnog lima (30/50/80), zidni (Z) ili zidni + podni (100) • Namenjen je za skladištenje tehničke vode • Postoji mogućnost ugradnje grejača sa regulacijom temperature od 2 do 4,5kW za bafer 50, 80 i 100l • Priključuje se na sistem grejanja. Jedna od značajnijih karakteristika je energetska efikasnost ovog proizvoda, energetski razred B za bafer 80 i 100l • Zidna varijanta 30, 50 i 80 litara. Zidna i podna varijanta 100 litara • Ugradnja priključaka sa strane (nivoi L1-L4) od 5/4".



100 litara



80 litara



50 litara



30 litara

Linija	Kazan	Grejač	Naziv proizvoda	V	Montaža	Ulaz/Izlaz	Odzraka	Ispust	Ts	EE	Izolacija
Bafer	Čelik	Ne	Buffer Tank 30-4 TPZ	30	Zidni	4x1"	1/2"	1/2"	/	C	PU
		Opciono 6/4"	Buffer Tank 50-4 TPZ	50	Zidni	4x5/4"	1/2"	6/4"	1/2"	C	PU
			Buffer Tank 80-8 TPZ	80	Zidni	8x5/4"	1/2"	6/4"	2x1/2"	B	PU
			Buffer Tank 100-8 TPU	100	Univerzalni	8x5/4"	1/2"	1/2"	2x1/2"	B	PU
			Buffer Tank 200-8 TPP	200	Podni	8x6/4"	3/4"	3/4"	4x1/2"	C	PU

Linija	Kazan	Grejač	Naziv proizvoda	V	Montaža	Ulaz/Izlaz	Odzraka	Ispust	Ts	EE	Izolacija
Bafer	Čelik	Opciono 6/4"	Buffer Tank 200-8 TPP	200	Podni	8x6/4"	3/4"	3/4"	4x1/2"	C	GR
			Buffer Tank 300-8 TPP	300	Podni	8x6/4"	3/4"	3/4"	4x1/2"	C	GR
			Buffer Tank 500-8 TPP	500	Podni	8x6/4"	3/4"	3/4"	4x1/2"	C	GR